



# RTK/RTCM Reference Station



**Compatible with any RTK/PPP System**

thanks to industry standard NTRIP



**Enables accurate RTK/PPP positioning**



**Provides corrections on satellite position and clock errors, code/phase biases & atmospheric delays**



## Cloud based RTCM Service

ensuring usability independent of any company's network policy



ANavS GmbH  
Gotthardstraße 40,  
80686 Munich

Phone: +49 (0) 89 89056721  
Fax: +49 (0) 89 89056720  
Email: [info@anavs.de](mailto:info@anavs.de)  
Web: <http://www.anavs.de>

## SPECIFICATIONS

**Enables accurate RTK/PPP-Positioning ( $1\sigma$ ):**

Horizontal accuracy: 0.006 m + 1 ppm

Vertical accuracy: 0.015 m + 1 ppm

### GNSS-Bands:

GPS: L1C/A, L1C, L1PY, L2C, L2P, L5

GLO: L1CA, L2CA, L2P, L3

GAL: E1, E5a, E5b, E5 AltBoc, E6

BDS: B1I, B1C, B2a, B2I, B3

QZSS: L1C/A, L1C, L2C, L5, L6

### Data:

Communication: NTRIP  
Format: RTCM 3.X  
Rate: up to 5 Hz

### Connectivity:

Ethernet, WLAN, LTE

### Mechanical:

Size: 227 x 169 x 56 mm  
Weight: 1200 g  
Operating Temp.: -25°C to +75°C  
Ingress protection: IP54

### Power-Supply:

230 V power plug  
USB Port (Type A)