



RTK/RTCM Reference Station



Compatible with any RTK/PPP System thanks to industry standard NTRIP



Enables accurate RTK/PPP positioning



Provides corrections on satellite position and clock errors, code/phase biases & atmospheric delays



Cloud based RTCM Service ensuring usability independent of any company's network policy



ANAVS GmbH
Gotthardstraße 40,
80686 Munich

Phone: +49 (0) 89 89056721
Fax: +49 (0) 89 89056720
Email: info@anavs.de
Web: <http://www.anavs.de>

SPECIFICATIONS

Enables accurate RTK/PPP-Positioning (1σ):

Horizontal accuracy: 0.006 m + 1 ppm

Vertical accuracy: 0.015 m + 1 ppm

GNSS-Bands:

GPS: L1C/A, L1C, L1PY, L2C, L2P, L5

GLO: L1CA, L2CA, L2P, L3

GAL: E1, E5a, E5b, E5 AltBoc, E6

BDS: B1I, B1C, B2a, B2I, B3

QZSS: L1C/A, L1C, L2C, L5, L6

Data:

Communication: NTRIP, TCP

Format: RTCM 3.X

Rate: up to 5 Hz

Connectivity: Ethernet, WLAN, LTE

Mechanical:

Size: 294 x 195 x 95 mm

Weight: 1200 g

Operating Temp.: -25°C to +75°C

Power-Supply:

230 V power plug

USB-C with PD (min. 18 W)